

# Moore 382 Logic and Sequence Controller Model Selection

	Model No. 3 8 2					
<b>Type</b>						
Basic	B					
Expanded	E					
<b>Power Requirement</b>						
120 Vac (+10%, -15%) 47 to 63 Hz (see note 1)	A					
24 Vac (+10%, -15%) 47 to 63 Hz	B					
24 Vdc (+20%, -15%)	C					
220/240 Vac (+10%, -15%) 47 to 63 Hz (see note 1)	E					
*Note 1: On newer models the "E" is no longer available. It is merged with "A"; 120/240 VAC (85 to 264 VAC) 47 to 63 Hz. Please specify your power input requirement.						
<b>Mounting Case</b>						
Screw Terminals, 20			1			
Screw Terminals, 40 (Required on 382E)			2			
Not Required			N			
<b>Operators Panel</b>						
Analog and Digital Displays				1		
Not Required (Blank Panel)				N		
<b>Third Input Options</b>						
Voltage (Additional 1 to 5 Vdc)					V	
Thermocouple (J, K, T, E, S, R, B) and Millivolt					T	
RTD (DIN curve; US curve)					D	
Frequency					F	
Computer (Dual Pulse and Pulse Direction)					C	
Not Required					N	
<b>Link Interface</b>						
Local Instrument Link (RS422, Half-Duplex)						1
Not Required						N
<b>Electrical Classification</b>						
CSA						C
FM						F
Not Available						N
	Model No. 3 8 2					
	B	A	1	1	V	1 F

Please let us know the exact model you require. We can often customize units for your specific needs.



Classic Automation LLC  
 800 Salt Road  
 Webster, NY 14580  
 USA

[www.classicautomation.com](http://www.classicautomation.com)

+1 (585) 241-6010

[customerservice@classicautomation.com](mailto:customerservice@classicautomation.com)